

Imagine

Construction	Tufted,, Pinpoint Saxony
Face Fiber	Invista Tactesse® Nylon Type 6,6
Yarn Finish	Superba® Heatset
Stain Repel / Stain Resist / Soil Release	Lotus FX™ Fiber Shield with Teflon® Protectant
Antimicrobial	AlphaSan® Built-In Protection
Tufted Face Weight	40 oz./sq.yd. (1,356.3 g./sq.m.)
Gauge	1/10 (39.4/10 cm.)
Stitches	15.0/in. (59.1/10 cm.)
Tufts	150.0/sq.in. (2,328.5/100 sq.cm.)
Finished Pile Height	0.22 in. (5.59 mm.)
Standard Backing	Endura-Loc™
Broadloom Size	13 ft., 6 in. (4.11 m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Recommended Maintenance	Capture® Carpet and Fabric Care
Indoor Air Quality – CRI Green Label Plus™	GLP2860, Carpet Category 1Y

Design Copyright - Milliken & Company
Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.
Copies of actual test results are available upon request.



Warranties:

- Lifetime Stain Resistance - Stainmaster Warranty
- Lifetime Soil Resistance - Stainmaster Warranty
- 20-Year Texture Retention - Stainmaster Warranty
- 20-Year Abrasive Wear - Stainmaster Warranty
- Lifetime Antistatic - Stainmaster Warranty
- 2-Year Limited Manufacturing Defects - Milliken Warranty

