



Atlas

PRODUCT SPECIFICATIONS

Style	T2402
Construction	Multi-level Cut Loop
Fiber	100% Solution-dyed Primus® PET Fiber
Gauge	1/10
Tufted Pile Weight	36 oz. / sq. yd.
Pile Height	0.312" / 0.250" / 0.0312"
Stitches Per Inch	16
Primary Backing	Woven Polypropylene
Secondary Backing	Actionbac®
Dye	Solution-dyed
Total Weight	72 oz.
Density	6660
Width	12'
Pattern Repeat	18"W x 21"L

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad. **Stretch-In Installation:** Establish roll sequencing, dry lay carpet, and apply latex seam sealer to both edges. Pre-stretch the sections with shorter pattern measurements to align with longer patterns in order to make hot melt seam (**use 6" tape to prevent seam peaking**). A two-headed power stretcher or "deadman" must be used to achieve this. Once the seam is made, proceed with proper stretch installation (CRI-104, figure "Stretch Diagram"). The use of architectural or double tackless strip is required to be used throughout a stretch-in installation.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution-dyed graphic and cut/loop patterns.

All specifications subject to normal manufacturing tolerance.

Tarkett North America

285 Kraft Drive
Dalton, GA 30721
USA: 800-871-3211

www.tarkettna.com

©Tarkett USA Inc. 10/2019