


MANUFACTURING SPECIFICATIONS

STYLE: Segment 26 oz Broadloom
CONSTRUCTION: Textured Loop
FIBER TYPE: Solution Dyed Nylon
WEIGHT: 26 oz/sq yard
DENSITY: 5318
GAUGE: 1/10
PATTERN REPEAT: None
SIZE: 12' Wide


STYLE: Segment Modular Tile
CONSTRUCTION: Textured Loop
FIBER TYPE: Solution Dyed Nylon
WEIGHT: 15 oz/sq yard
DENSITY: 5493
GAUGE: 1/10
PATTERN REPEAT: None
SIZE: 24" x 24" Tile

CORNER TILE TABS AVAILABLE FOR INSTALLATION WITHOUT ADHESIVE


INSTALLATION METHODS:




Monolithic



Quarter Turn



Ashlar



Brick

PERFORMANCE CHARACTERISTICS

FLAMMABILITY: <450 Flaming / Class I Fire Rated
STATIC (AATC 134): < 3.0 K.V.

NO ZIPPERING

WARRANTIES

- Lifetime Fiber Performance for Wear & Static
- Lifetime Stain Removal
- Lifetime Colorfastness to Light & Atmospheric Contaminants
- Lifetime for Tuft Bind Strength (edge ravel, yarn pulls, zippering)

SEE CONSUMER WARRANTY BROCHURE FOR DETAILS.

Color may vary from dye lot to dye lot.

Substitution of material may be made due to improved technology, supply limitations or other factors