

TERRAIN & TOPOGRAPHY MANUFACTURING SPECIFICATIONS

PILE YARN CONTENT: 100% Solution Dyed Nylon
GAUGE: 1/12
SURFACE APPEARANCE: Textured Patterned Loop
DENSITY: 6,585
BACKING: UltraSet Matrix
WIDTH: 24" x 24"
INSTALLATION METHOD: Monolithic / Vertical Ashlar / Brick Ashlar /
. Quarter Turn / Multi-Directional

PERFORMANCE CHARACTERISTICS

FLAMMABILITY: ASTM E 648 Class I
PILL TEST: Passes
STATIC (AATC 134): Under 3.5 K.V.
SMOKE DENSITY (E-662): Less than 450
IAQ GREEN LABEL PLUS: Certified

WARRANTY INFORMATION

Lifetime Limited Wear Warranty
Lifetime Limited Static Protection Warranty
Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional
Stability Warranty
Lifetime Limited Colorfastness to Light Warranty
10 Year Limited Stain Resistance Warranty

SEE CONSUMER WARRANTY BROCHURE FOR DETAILS.

Color may vary from dye lot to dye lot.

Substitution of material may be made due to improved technology, supply limitations or other factors