

NuGen™ Click

RIGID CORE

Rigid.
Flexible.
Beautiful.

NuGen combines the best of both worlds. Rigid core flooring that is also more flexible and easier to manage than similar products.

Use in Any Room

Waterproof so it's safe to use in kitchens, bathrooms, or laundry rooms.

Install Immediately

No acclimation time required. Buy and install immediately after purchase.

Rigid Core

Overcomes subfloor imperfections and telegraphing, unlike traditional luxury vinyl tile.

Durable

Stands up to kids, pets, high heels and heavy furniture.

Fast and Easy to Install

NuGen's fast-locking click system ensures a low-cost, low-mess installation – even over existing floors! No power tools required.

Quiet Under Foot

The acoustical backing provides superior sound absorption and overall comfort.



WATERPROOF



EASE OF
MAINTENANCE



DURABILITY




UNICLIC
EASY TO
INSTALL


ALSACE OAK | LIMED NATURAL
270285008

 **Tarkett**

NuGen™ Click




Wessex Rail
Ligna
270285000




Teak Marado
Natural
270285001




Sparrow Oak
Gray Pearl
270285002




Milled Oak
Sun Toned
270285003




Mineral Oak
Long Grain
270285004




Chestnut Ridge
Furrowed
270285005




Pecan Flame
Claro
270285006



Cottage Plank
Bella
270285007




Alsace Oak
Limed Natural
270285008



Driftwood
Sand
270285009

Specifications	
Nominal Thickness	0.177" (4.5 mm)
Wear Layer Thickness	0.012" (0.3 mm)
IXPE Acoustical Backing	1mm
Finish Edge	Square
Finish	Polyurethane
Material	Phthalate Free, 100% Virgin Material
Reusable Content	100% Reclaimable
Scratch/Scuff/Abrasion Properties	Excellent
Dimensional Stability	ASTM F2199 Passes
Static Load Limit	ASTM F970 Passes
Residual Indentation	ASTM F1914 Passes (PSI Equivalent > 5,000 lbs.)
Slip Resistance	ASTM D2047 ≥ 0.5 SCOF
Fire	ASTM E648 ≥ .45 w/cm ²
Smoke	ASTM E662 ≤ 450
Heat Stability	ASTM F1514 Δ E ≤ 8
Light Stability	ASTM F1515 Δ E ≤ 8
Staining	ASTM F925 Passes
Installation System	UniClic Locking System
FloorScore® Certification	Certified
Size	7.13" x 48.03" (181mm x 1220mm)
Pieces per Carton	12 Planks
Weight per Carton	Planks: 39.47 lbs. (17.9 kgs.)
Area per Carton	28.52 sq. ft. (2.65 m ²)
Cartons per Pallet	55

Accessories



T-Molding

Ensures a smooth transition between flooring at the same height.



Universal Reducer

Makes an attractive and safe transition between flooring of different heights.



Flush Mount Stair Nose

Provides a smooth transition for stairway steps, or when leading toward stairs, a sunken living room, or balcony overlook.



Phthalate Free



Tarkett North America

30000 Aurora Road
Solon, OH 44139
USA: 1-877-TARKETT (1-877-827-5388)
Canada: 1-877-436-6267

www.tarkettna.com

For more accurate color and pattern representation, we suggest you visit an authorized Tarkett dealer to view an actual product sample.

©Tarkett USA Inc. 08/2019