



Polyethylene Foam Underlayment

NRF select **PE 2000** is an economy grade laminate and wood flooring foam underlayment that provides moisture protection, sound control and warmth. **PE 2000** protects the life of your floor.

Approved For Use Under:

- Laminate
- Solid Hard Wood Floors
- Engineered Wood Floors
- Bamboo Floating Floors



PE 2000

POLYETHYLENE FOAM UNDERLAYMENT



APPROVED FOR USE UNDER:

- Laminate
- Solid Hardwood Floating Floors
- Engineered Wood Floating Floors
- Bamboo Floating Floors

APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Approved Interior Subfloors

PRODUCT FEATURES:

- Sound Abatement
- Moisture Protection
- Lip and Tape
- 1-Year Limited Warranty
- Economical
- Comfort
- Easy Installation

PE 2000 is an economy grade laminate and wood flooring foam underlayment that provides moisture protection, sound control and warmth. **PE 2000** protects the life of your floor.

APPLICATION: Residential flooring.

DIMENSIONS AND PACKAGING:

- Roll Size = 250 sq ft
- Roll Dimensions = 48" x 62.5'
- Rolls Per Pallet= 100
- Rolls Per Truck= 3000

PHYSICAL PROPERTIES:

- Material = Polyethylene Foam
- Thickness (mm) = 2.0
- Joining System = Lip and Tape

INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Underlayment with lip and tape- join seams together, overlap the film lip and attach to the adhesive bead. Remove tape release liner before applying film lip.

