



# Poly Vapor Barrier

6 mil Polyethylene Vapor Barrier provides moisture protection for flooring that has the pad attached. It can also be used as extra moisture protection under most floating floor installations.

## Approved Substrates:

- Cured Concrete
- APA Grade Plywood
- OSB



## 6 MIL POLYETHYLENE VAPOR BARRIER



**NRF Select 6 MIL Polyethylene Vapor Barrier** provides moisture protection for flooring that has the pad attached. It can also be used as extra moisture protection under most floating floor installations.

**APPLICATION:** Approved for commercial and residential flooring.

### DIMENSIONS AND PACKAGING:

PE 6006

- Roll Size = 45,000 sq ft  
(6 rls/case, 25 cases/pallet)
- Roll Dimensions = 6' x 50'

PE 10006

- Roll Size = 56,000 sq ft  
(56 rolls/pallet)
- Roll Dimensions = 10' x 100'

### APPROVED FOR USE UNDER:

- All Floating Floors with Attached Pad
- Traditional Floating Floors

### APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Grade Plywood

### PRODUCT FEATURES:

- 6 Mil Vapor Barrier
- SKU: PE 6006 & PE 10006
- Low Density Film
- Moisture Protection
- Made in the USA

### PHYSICAL PROPERTIES:

- Material = Polyethylene Resin
- Weight = 50 lbs per roll
- Density (lbs./cu ft) = 0.922g/cm<sup>3</sup>
- Thickness (mm) = 6 mil

### INSTALLATION INSTRUCTIONS:

1. Cut sheets to the length of room.
2. If desired, tape seams with quality packaging tape.



NRFSELECT.COM

