



Premium Foam Underlayment

PP 3020 is specifically built to address the new flooring products on the market today. **PP 3020** can be used under all Laminate and Wood flooring products. The new low profile, high density, waterproof foam can be used under attached pad flooring for additional sound abatement or moisture protection as needed.

Approved For Use Under:

- Laminate
- Solid Hard Wood Floors
- Engineered Wood Floors



PP 3020 PREMIUM FOAM UNDERLAYMENT



APPROVED FOR USE UNDER:

- Laminate
- Solid Hardwood Floating Floors
- Engineered Wood Floating Floors
- Bamboo Floating Floors

APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Approved Interior Subfloors

PRODUCT FEATURES:

- Sound Abatement
- Moisture Protection up to 75% RH
- LapWise™ Seam Sealing Technology
- Recyclable
- 20-Year Limited Warranty
- Made in the USA

SoundWise™ PP 3020 is specifically built to address today's challenging floating floor installations. This premium foam underlayment is a waterproof non-cross linked technology that can be used under all laminate and hardwood floating floors. This Premium Underlayment provides moisture protection, sound abatement, and overall high density stability. It has the highest Delta rating in the industry in this category.

APPLICATION: Approved for commercial and residential flooring.

DIMENSIONS AND PACKAGING:

- Roll Size = 250 sq ft
- Roll Dimensions = 42" x 71.5'

PHYSICAL PROPERTIES:

- Material = Polypropylene Foam (non-xlink)
- Density (lbs./cu ft) = 3.0
- Thickness (mm) = 2.0
- Compression Strength (psi@50%) = 13.6
- Moisture Vapor Emissions Rate = 0.00000338 (lbs/m²/24hrs)
- Joining System is LapWise™ Technology

INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Roll out second row, overlap LapWise™ seam 2".
6. Remove release liner and press LapWise™ seam together.

SOUND TEST:

IIC	STC	DELTA	FLOOR	SUBFLOOR
67	63	26	LVP	6" CONCRETE W/ CEILING



WRFSELECT.COM

