



# Fiber Underlayment

**NRF Select Soft Step Recycled Fiber Underlayment** is an excellent choice when installing a recycled product is important. It is made in the USA with 100% recycled fibers. NRF Select Soft Step has excellent foot fall performance making hard surface floors sound solid and quiet.

## Approved Substrates:

- Cured Concrete
- APA Grade Plywood
- OSB



# Soft Step

RECYCLED FIBER UNDERLAYMENT

**NRF Select Soft Step** Recycled Fiber Underlayment is an excellent choice when installing a recycled product is important. It is made in the USA with 100% recycled fibers. **NRF Select Soft Step** has excellent foot fall performance making hard surface floors sound solid and quiet.

## APPLICATION:

Approved for commercial and residential flooring.

## PRODUCT FEATURES:

- Sound Abatement
- Moisture Protection
- 20-Year Limited Warranty
- Made in the USA

## PHYSICAL PROPERTIES:

- Material = Recycled Fiber
- Density (lbs./cu.ft) = 9
- Thickness = 0.165"
- Compression Strength (psi) = 4.6
- Moisture Vapor Emissions Rate = 0.28 PERMS

## DIMENSIONS AND PACKAGING:

- Roll Size: 100.1 sq ft

## SOUND TEST:

IIC	STC	DFI TA	FLOOR	SUBFLOOR
70	65	N/A	Laminate	Concrete

## APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Approved Interior Subfloor



## APPROVED FOR USE UNDER:

- Laminate
- Solid Hardwood Floating Floors
- Engineered Floating Floors

## INSTALLATION INSTRUCTIONS:

1. Clean sweep or vacuum subfloor of all debris.
2. Check the subfloor. It should be clean, dry and level.
3. Roll out the underlayment length of the room.
4. Line up seams close together; do not overlap.
5. Tape seams together with packaging tape.



SCAN ME

